



# Ledinaire floodlights gen3

## BVP165 LED180/840 PSU 150W SWB CE

-- 840 neutral white -- -- Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

### Product data

General information		Number of products on MCB of 16 A type B	
Lamp family code	-		15
Light source color	840 neutral white	Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Light source replaceable	No	Photobiological risk specification	0.2 m
Number of gear units	1 unit	EU RoHS compliant	Yes
Driver/power unit/transformer	-	Light source engine type	LED
Driver included	Yes	Service tag	No
Optical cover/lens type	Glass	<b>Light technical</b>	
Luminaire light beam spread	110° x 110°	Upward light output ratio	0
Control interface	-	Standard tilt angle posttop	-
Connection	Flying leads/wires	Standard tilt angle side entry	-
Cable	Cable 2.0 m without plug	<b>Operating and electrical</b>	
Protection class IEC	Safety class I	Input Voltage	220 to 240 V
Flammability mark	-	Input Frequency	50 or 60 Hz
CE mark	Yes	Initial CLO power consumption	- W
ENEC mark	-	Average CLO power consumption	150 W
Warranty period	3 years	End CLO power consumption	- W
Optic type outdoor	Symmetrical		
Constant light output	No		

## Ledinaire floodlights gen3

Inrush current	4.16 A
Inrush time	0.0264 ms
Power Factor (Min)	0.95

### Controls and dimming

Dimmable	No
----------	----

### Mechanical and housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	282 mm
Overall width	409 mm
Overall height	32.5 mm
Effective projected area	0.077 m <sup>2</sup>
Color	Gray
Dimensions (Height x Width x Depth)	33 x 409 x 282 mm

### Approval and application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]
Surge Protection (Common/Differential)	4/4 kV
Sustainability rating	-

### Initial performance (IEC compliant)

Initial luminous flux (system flux)	18000 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	150 W
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

### Over time performance (IEC compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	80

### Application conditions


Ambient temperature range	-25 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

### Product data

Full product code	871951453350999
Order product name	BVP165 LED180/840 PSU 150W SWB CE
EAN/UPC - Product	8719514533509
Order code	911401857483
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401857483
Net Weight (Piece)	2.740 kg



## Dimensional drawing



BVP165 LED180/840 PSU 150W SWB CE

## Ledinaire floodlights gen3

