Product data sheet Characteristics

EVP1CNS32121

EVlink Charging cable 5m 32A 1-Phase T2-T1 IEC EV accessory



Main

EVlink	
Charging cable	
Cabling accessory	
Single phase	
1P + N	
32 A	
220240 V AC 50/60 Hz	
2	
	Charging cable Cabling accessory Single phase 1P + N 32 A 220240 V AC 50/60 Hz

Complementary

Connector type	T2 charging station end silver plated contacts T1 vehicle end silver plated contacts	
Range compatibility	EVlink (EVlink parking) EVF1 charging station EVlink (EVlink parking) EVW1 charging station EVlink (EVlink parking) EVF2 charging station EVlink (EVlink parking) EVW2 charging station EVlink (EVlink Smart Wallbox) EVB1 charging station EVlink (EVlink Wallbox) EVH2 charging station	
Standards	IEC 62196-1 IEC 62196-2	
Product certifications	CE	
Length	5 M	
Net weight	2.4 Kg	

Environment

IP degree of protection	IP44 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Ambient air temperature for operation	-3050 °C	
Ambient air temperature for storage	-4080 °C	
Relative humidity	595 %	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8 Cm	
Package 1 Width	36 Cm	
Package 1 Length	44 Cm	
Package 1 Weight	2.425 Kg	

Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30 Cm
Package 2 Width	40 Cm
Package 2 Length	60 Cm
Package 2 Weight	10.597 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	16
Package 3 Height	75 Cm
Package 3 Width	60 Cm
Package 3 Length	80 Cm
Package 3 Weight	48.5 Kg

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	[™] China RoHS Declaration	
RoHS exemption information	€Yes	

Product Life Status : Commercialised

