

# 4 THREADED BARS 160A L1400/ LINERGY BS BB

04171

- Discontinued on: 20 January 2022
- End-of-service on: 20 January 2022

! Discontinued

#### Main

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma G enclosure Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

#### Complementary

Complementary	
Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ui] rated insulation voltage	1000 V
[le] rated operational current	160 A
[lpk] rated peak withstand current	30 kA
I²t on activation	100000 kA².s
Busbar cross section	15 x 5 mm
Length	1400 mm
Net weight	3.74 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm
Support thickness	5 mm

#### **Environment**

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.74 kg
Package 1 Height	2.2 cm
Package 1 width	13 cm
Package 1 Length	150 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	56
Package 2 Weight	209.44 kg
Package 2 Height	28.5 cm
Package 2 width	200 cm
Package 2 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

#### Recommended replacement(s)

04171 is replaced by:

1x

3 3

4 THREADED BARS 160A L1400/LINERGY BS BB

LVS04171