

# Product data sheet

Specifications



## ARGUS standard outdoor 120° - blister

CCTR1PB04

! Discontinued on: 15 December 2020

! Discontinued

### Main

Range of product	ARGUS standard movement detector
Range	ARGUS
Product or component type	Movement detector
Load type	Incandescent lamp: 1000 W, AC Low voltage halogen lamp with wire-wound transformer: 500 VA Low voltage halogen lamp with electronic transformer: 250 VA Fluorescent tube: 200 VA, AC Compact fluorescent lamp: 3 x 23 W, AC Capacitive: : 6 A, 21 µF, AC Capacitive: : 10 A, 14 µF, AC Halogen lamp: 900 W, AC
Colour tint	White
Type of packing	Blister

### Complementary

[Ue] rated operational voltage	220...240 V
Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V
Output current	10 A
Type of setting	Light sensitivity adjustable Time adjustment
Time delay	3 s...30 min
Light intensity adjustment	5...2000 lux
Horizontal detection angle	0...120 °
Detection range	Frontal: 12 m
Material	PC (polycarbonate) matt
Device mounting	Surface
Mounting height	2.5 m

### Environment

IP degree of protection	IP55
Ambient air temperature for operation	-15...40 °C

## Packing Units

Package 1 Weight	301.000 g
Package 1 Height	236.000 mm
Package 1 width	83.000 mm
Package 1 Length	173.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)

CCTR1PB04 is replaced by:

1x



ARGUS standard outdoor 120° - carton  
CCT56P004