2 YEAR WARRANTY

EFET™ 330 (-10°C to 10° C)

The EFET™ 330 is an electronic thermostat to be installed in electric cabinets with DIN rail attachment. Used primarily for controlling a lower temperature range as by frost protection.

The thermostat must be installed via an all-pole disconnection switch and has a LED indicating the current mode (heating, standby or fault).

To measure and control the desired temperature a wire sensor or an outdoor air sensor must be used. The temperature setting can be adjusted with a scale from -10° C to +10°C.

Benefits:

- For DINrail mounting
- Low temperature area
- Low standby consumption
- LED indicator

Standard compliance:

- EN/IEC 60730-1 (general), EN/IEC 60730-2-9 (thermostat)

Approvals:

Type	Value
Operation voltage	220 V- 240V~ 50/60 Hz
Standby power consumption	max. 0.25 W
Relay: Resistive load Inductive load	 Max 16A / 3680W @ 230V Cos Φ = 0.3 max. 1A
Sensing unit	NTC 15 kOhm at 25° C
Hysteresis	± 0.2° C
Ambient temperature	-10° C to +50° C
Lowering in economy periods	5° C
Temperature range	-10° C to +10° C
Cable specification max	1 x 4 mm² or 2 x 2,5 mm²
Ball pressure test temperature	75° C
Pollution degree	2 (domestic use)
Controller type	1 C
Storage temperature	-20° C to +65°C
IP class	20
Protection class	Class II - ⧈
Dimensions (H/W/D)	85 mm x 36 mm x 58 mm
Weight	83 g

Types

Item no.	Product name	Type	EAN no.
088L0444	EFET™ 330	Temp. range -10° C to +10° C, incl. floor sensor	5703466209219